Page: 1/5

ISO ALCOOL 70%

1. IDENTIFICATION

Product name : ISO ALCOOL 70%

Product code : 09-10076 Other means of identification : Not available.

 Supplier
 : Sani-Marc Inc.
 Manufacturer
 : Sani-Marc Inc.

 42 rue de l'Artisan
 42 rue de l'Artisan
 42 rue de l'Artisan

 42 rue de l'Artisan
 42 rue de l'Artisan

 Victoriaville, Qc
 Victoriaville, Qc

 G6P 7E3
 G6P 7E3

 1-819-758-1541
 1-819-758-1541

sanıtızer

Approved for use in Food & Beverage plants.

Date of issue (YYYY-MM-DD) : 2021-05-03

In case of emergency : Emergency phone: CANUTEC (613) 996-6666 (Collect calls accepted)

2. HAZARDS IDENTIFICATION

Information in this section only concerns the product as supplied. Contact your account manager to get more information on diluted form hazards identification.

Product Classification : FLAMMABLE LIQUIDS - Category 2

EYE IRRITATION - Category 2B

Signal word : Danger Hazard pictograms



Hazard statements : Highly flammable liquid and vapors.

Causes eye irritation.

Precautionary statements

Prevention : Wear protective gloves. Wear protective clothing. Wear eye or face protection: Recommended: Safety Glasses. Keep away from heat,

hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash thoroughly after handling.

Response : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice

or attention.


Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : No additional information.

Other hazards which do not result in : None known.

classification



4. FIRST AID MEASURES

Description of required first aid measures

Eye contact In case of contact with eyes, flush with fresh water. Check for and remove any contact lenses. Continue rinsing. If irritation persists,

get medical attention.

Skin contact In case of irritation, rinse with water. Get medical attention if irritation persist.

Ingestion Rinse mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

Inhalation Move victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if adverse health effects persist

or are severe. Maintain an open airway.

Most important symptoms/effects, acute and delayed

Eye contact Adverse symptoms may include the following:

irritation watering redness

Skin contact No specific symptoms under normal use conditions.

 Ingestion
 No specific symptoms under normal use conditions.

 Inhalation
 No specific symptoms under normal use conditions.

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See toxicological information (Section 11)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the

chemical

Highly flammable liquid and vapors. In a fire or if heated, a pressure increase will occur and the container may

burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition

products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special fire-fighting

procedures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action should be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-

fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with

a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Initiate spill response procedures if required.

Personal protection Put on appropriate personal protective equipment (see Section 8).

Cleaning method Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and

place in container for disposal according to local regulations (see Section 13). Use a water rinse for final clean-up.



ISO ALCOOL 70% Page: 2/5

7. HANDLING AND STORAGE

Handling

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See Section 8 for additional information on hygiene measures.

Storage and Incompatibility

Store in accordance with local regulations. Store in a segregated and approved area. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Keep out of reach of children. Store away from incompatible materials (see Section 10).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

Ingredient name	Exposure limits
propan-2-ol	CA Alberta Provincial (Canada, 4/2009).
	15 min OEL: 984 mg/m ³ 15 minutes.
	8 hrs OEL: 200 ppm 8 hours.
	15 min OEL: 400 ppm 15 minutes.
	8 hrs OEL: 492 mg/m ³ 8 hours.
	CA British Columbia Provincial (Canada, 6/2017).
	TWA: 200 ppm 8 hours.
	STEL: 400 ppm 15 minutes.
	CA Ontario Provincial (Canada, 7/2015).
	TWA: 200 ppm 8 hours.
	STEL: 400 ppm 15 minutes.
	CA Quebec Provincial (Canada, 1/2014).
	TWAEV: 400 ppm 8 hours.
	TWAEV: 983 mg/m ³ 8 hours.
	STEV: 500 ppm 15 minutes.
	STEV: 1230 mg/m³ 15 minutes.
1	CA Saskatchewan Provincial (Canada, 7/2013).
	STEL: 400 ppm 15 minutes.
	TWA: 200 ppm 8 hours.

Appropriate engineering controls

For manufacturing or industrial uses it can be appropriate to: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.

Individual protection measures

Eye/face protection

Continued or intense exposures might required to wear safety glasses. It is minimally suggested to wear safety glasses while using or handling this product.

Hands and Body protection

No specific protective equipment required under normal use conditions. Prolonged or severe exposures might require to wear chemical-resistant gloves.

No special protective clothing is required.

Respiratory protection No specific protective equipment required under normal use conditions.

9. PHYSICAL AND CHEMICAL PROPERTIES							
Physical state	Liquid. [Transparent liquid.]	рН		Not available.	Flash point		Closed cup: 11.6°C (52.9°F) [Tagliabue.] Open cup: 30°C (86°F) [Cleveland]
Color	Colorless. [Transparent]	Relative density		0.856	Melting point		-88.5°C (-127.3°F)
Odor	Alcohol like.	Viscosity		Not available.	Boiling point		82.5°C (180.5°F)
Odor threshold	Not available.	Vapor pressure		Not available.	Fire point	:	Not available.
Solubility in water :	Not available.	Vapor density	:	Not available.	Evaporation rate	:	Not available.
Decomposition temperature : Not available.			Auto-ignition temperature	e : 399°C (750.2	2°F	·)	



ISO ALCOOL 70% Page: 3/5 Partition coefficient: n-octanol/ : Not applicable.

water

Flammability (solid, gas)

Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidizing

materials.

Flammable in the presence of the following materials or conditions: combustible

materials.

Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition, it emits acrid smoke and fumes.

Flammable.

Lower and upper explosive (flammable) limits : Lower: 2.5%

Upper: 12%

10. STABILITY AND REACTIVITY

Reactivity No specific test data related to reactivity available for this product or its ingredients.

Chemical stability The product is stable.

Incompatible materials Reactive or incompatible with the following materials:

oxidizing materials

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Route of Routes of entry anticipated: Oral, Dermal, Inhalation.

exposure

Potential acute health effects Symptoms

Eye contact May cause eye irritation. Adverse symptoms may include the following:

irritation watering redness

Skin contact No known significant effects or critical No specific symptoms under normal use conditions.

hazards.

No known significant effects or critical No specific symptoms under normal use conditions.

hazards.

Inhalation No known significant effects or critical No specific symptoms under normal use conditions.

hazards.

Toxicity data

Ingestion

Product/ingredient name	Result	Species	Dose	Exposure
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Information on toxicological effects

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Sensitization Not available.

Carcinogenicity No known significant effects or critical hazards.




ISO ALCOOL 70% Page: 4/5

12. ECOLOGICAL INFORMATION				
Ecotoxicity data				
Product/ingredient name		Result	Species	Exposure
propan-2-ol		Acute EC50 10100 mg/l Fresh water Acute LC50 1400000 μg/l Marine water Acute LC50 4200 mg/l Fresh water	Daphnia - Daphnia magna Crustaceans - Crangon crangon Fish - Rasbora heteromorpha	48 hours 48 hours 96 hours
Persistence and degradability	: Unknown	Bioaccumulative potential : Unknown Mobility in soil	: Unknown Other adverse e	ffects : Unknown

	13. DISPOSAL CONSIDERATIONS
Disposal methods	Dispose content and container in accordance with local, regional and national regulation in force.

14. TRANSPORT INFORMATION					
	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	TDG Placard
TDG Classification	UN1993	UN 1993 FLAMMABLE LIQUIDS N. O.S. (Isopropyl alcohol)	3	II	
Product classified as per	the following section	ons of the Transportation of Dangero	us Goods Regulations: 2.18-2	.19 (Class 3).	
Additional nformation	See shipping docur	nents for specific information on DOT	Γ, IMDG or IATA		

15. REGULATORY INFORMATION				
Canadian lists				
Canadian NPRI	None of the components are listed.			
CEPA Toxic substances	None of the components are listed.			
Canada inventory	At least one component is not listed.			
International lists				
United States Not determined.				



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



ISO ALCOOL 70% Page: 5/5