# **BUSCH TR-034**

#### 000003001076

Version 3.1



Revision Date 2019/02/01

Print Date 2019/02/01

#### **SECTION 1. IDENTIFICATION**

Product name	:	BUSCH TR-034

Product code : 831.034.500ml

Manufacturer or supplier's deta	ails Busch Vacuum Technics Inc. 1740 boul. Lionel-Bertrand Boisbriand, Québec Canada J7H 1N7
Emergency telephone number	
Emergency telephone number :	Busch: 450-435-6899 / 1-800-363-6360 CHEMTREC Transport Emergency: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the chen	nical and restrictions on use
Recommended use :	Busch TR-034 is a lubricant for vacuum pumps. Not to be used in conditions where aerosols could be generated.
Prepared by :	Busch: 450-435-6899 / 1-800-363-6360

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	viscous liquid
Colour	dark red
Odour	Mild petroleum oil like.

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### **Potential Health Effects**

Primary Routes of Entry	:	Eye contact Ingestion Inhalation Skin contact
Aggravated Medical Condi- tion	:	None known.

# BUSCH TR-034

#### 000003001076

Version 3.1



Revision Date 2019/02/01

Print Date 2019/02/01

# Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture		Mixture
	•	IVIIALUIC

## Components

Chemical name	CAS-No.	Concentration (% w/w)
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	30 - 50
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	30 - 50
Methacrylate copolymers		1 - 5
Sulfurized long-chain alkyl acid ester		1 - 5
Ethanol, 2,2'-iminobis-, N-tallow alkyl derivs.	61791-44-4	0.1 - 0.25

#### SECTION 4. FIRST AID MEASURES

If inhaled :	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact :	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact :	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed :	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.

# **BUSCH TR-034**

### 000003001076



Version 3.1	Revision Date 2019/02/01	Print Date 2019/02/01
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.	

#### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), hydrocarbons, smoke and irritating vapours as products of incomplete com- bustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

# BUSCH TR-034

### 000003001076



Version 3.1	Revision Date 2019/02/01	Print Date 2019/02/01
Conditions for safe storage :	Avoid contact with skin, eyes and clot Do not ingest. Keep away from heat and sources of Keep container closed when not in us Store in original container. Containers which are opened must be	ignition. e.
	kept upright to prevent leakage. Keep in a dry, cool and well-ventilated Keep in properly labelled containers. To maintain product quality, do not sto light.	l place.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

# BUSCH TR-034

### 000003001076



000003001076		
Version 3.1	Revision Date 2019/02/01	Print Date 2019/02/01
Remarks	<ul> <li>Chemical-resistant, impervious gl approved standard should be wor chemical products if a risk assess essary.</li> </ul>	n at all times when handling
Eye protection	: Wear face-shield and protective s problems.	uit for abnormal processing
Skin and body protection	: Choose body protection in relation tration and amount of dangerous cific work-place.	
Protective measures	: Wash contaminated clothing befo	re re-use.
Hygiene measures	: Remove and wash contaminated ing the inside, before re-use. Wash face, hands and any expos handling.	

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	dark red
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-51 °C (-60 °F)
Boiling point/boiling range	:	No data available
Flash point	:	185 °C (365 °F) Method: Cleveland open cup
Fire Point	:	205 °C (401 °F)
Fire Point Evaporation rate	:	205 °C (401 °F) No data available
		No data available
Evaporation rate	:	No data available No data available
Evaporation rate Auto-ignition temperature Upper explosion limit / Upper	:	No data available No data available No data available
Evaporation rate Auto-ignition temperature Upper explosion limit / Upper flammability limit Lower explosion limit / Lower	:	No data available No data available No data available

# **BUSCH TR-034**

### 000003001076



Version 3.1		Revision Date 2019/02/01 F	Print Date 2019/02/01
Relative density	:	No data available	
Density	:	0.855 kg/l (15 °C / 59 °F)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	34.26 cSt (40 °C / 104 °F)	
		7.7 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurise, cut, weld, braze, solde pose containers to heat or sources of ign	

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, reducing agents and acids.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

Information on likely routes of	:	Eye contact
exposure		Ingestion
		Inhalation
		Skin contact

### Acute toxicity

Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Assessment: The substance or mixture has no acute inhala- tion toxicity Remarks: No data available
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available

#### **Components:**

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

# **BUSCH TR-034**

### 000003001076



sion 3.1			
		Revision Date 2019/02/01	Print Date 2019/0
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
		<b>5-30, hydrotreated neutral oil-based:</b> LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
<u>Product:</u> Remarks	:	No data available	
Serious eye damage/eye irr	itati	on	
<u>Product:</u> Remarks	:	No data available	
Respiratory or skin sensitis	satio	on	
No data available			
Germ cell mutagenicity No data available			
Carcinogenicity			
No data available			
No data available Reproductive toxicity			
Reproductive toxicity			
Reproductive toxicity No data available STOT - single exposure			

Product:

Toxicity to fish

: Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

# **BUSCH TR-034**

### 000003001076



Version 3.1	Revision Date 2019/02/01	Print Date 2019/02/01
aquatic invertebrates		
Toxicity to algae :	Remarks: No data available	
Toxicity to microorganisms :	Remarks: No data available	
Persistence and degradability		
Product:		
Biodegradability :	Remarks: No data available	
Bioaccumulative potential		
No data available		
Mobility in soil		
No data available		
Other adverse effects		
No data available		

### SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

· · · · · · · · · · · · · · · · · · ·	
Waste from residues	: The product should not be allowed to enter drains, water courses or the soil.
	Offer surplus and non-recyclable solutions to a licensed dis- posal company.
	Waste must be classified and labelled prior to recycling or disposal.
	Send to a licensed waste management company.
	Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### **National Regulations**

**TDG** Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:				
DSL	:	On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the		

# BUSCH TR-034

#### 000003001076



Version 3.1	Revision Date 2019/02/01 Print Date 2019/02/01	02/01
	TSCA Inventory or are in compliance with a TSCA Inventor exemption.	ory
IECSC	: On the inventory, or in compliance with the inventory	
EINECS	: On the inventory, or in compliance with the inventory	

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	•	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA QC OEL	:	Québec. Regulation respecting occupational health and safe- ty, Schedule 1, Part 1: Permissible exposure values for air- borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA QC OEL / TWAEV		Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations: DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response: ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

## BUSCH TR-034

000003001076



Revision Date

: 2019/02/01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN